











Analog Infrared Bullet Camera

- 480 TVL color infrared bullet camera
- 4~9 mm varifocal lens
- Weatherproof (IP66)
- Electronic day/night
- 125 feet zero lux illumination
- 12 VDC



Style	License plate recognition bullet	550 TVL Resolution
Signal System	NTSC/PAL	
Horizontal Resolution (D/N)	550 TVL day / 600 TVL night	 Auto Iris
Image Sensor	1/3" Double Scan CCD	
Picture Elements	NTSC: 768 (H) x 494(V) PAL: 752 (H) x 582 (V)	 Varifocal
Lens	2.8-11 mm varifocal	
FOV Degrees (Horizontal/Vertical)	81.2°(H)/65.4°(V) ~ 24.6°(H)/18.5°(V)	 Infrared
Auto Iris	Yes	
Min. Illumination (day)	Color (day) 0.01 lux f1.2	 Day/Night
Min. Illumination (night)	B/W (night) 0.00001 lux f1.2	
IR Beam Distance	150 ft.	 TRUE Day/Night
Infrared	Yes	
Day/Night (Electronic)	Yes	 OSD MENU
True Day/Night	Yes	
Scanning System	2:1 interlaced	 3D NR
Signal-to-Noise Ratio	≥52 dB (AGC off)	
Synchronization	Internal	
Gamma Correction	0.45 approx (OSD)	
Back Light Compensation	Yes	
White Balance	Yes	
On-Screen Display	Yes	
Extra Spot Monitor Output	Yes	
PoUTP	-- --	
DNR (Digital Noise Reduction)	Yes (3DNR)	
WDR (Wide Dynamic	-- --	

Range)		 3-Way Gimbal
IR Cut Filter (Mechanical)	Yes	
3 Way Axis Gimbal	Yes	
Communication	RS485 (Pelco D)	
ACCESSORIES		
Bracket	Yes	 IP67
Sun Shield	Yes	
Remote Control	-- --	 12VDC/24VAC Dual Voltage
Power Pigtail Lead	Yes	
ENVIRONMENTAL		
Operation Temperature	14°F to 122°F (-10°C to 50 °C)	
Storage Temperature	-22°F to 140°F (-30°C to 60 °C)	
Operating Humidity	Up to 95%	
Ingress Protection Rating (IEC 60529)	IP67	
Weatherproof	Yes	
Vandal Proof	Yes	
ELECTRICAL		
Video Out	Composite signal 1.0Vp-p/75ohm	
Signal Connector	BNC	
Input Voltage	12 VDC/24 VAC	
Current Draw	500 mA	
Power Consumption	6 Watts	
PHYSICAL		
Dimensions (W x H x D)	12" x 3.6" x 3.82" (304.7 x 91.5 x 97 mm)	
Weight	4.85 lb (2200 g)	
Housing Material	Powder coat	
Housing Color	Black	
Camera Mounting	Wall/ceiling	
REGULATORY		
Regulatory Type	CE, FCC, UL	

Warranty

10 Years