

Analog Covert Camera 'Clock'

- Covert Camera
- 550 TVL Resolution
- 3.7 mm Fixed Lens
- 12 VDC



Style	Clock	<div style="background-color: #ff9900; color: black; padding: 5px; text-align: center;">550 TVL</div> <div style="background-color: black; color: white; padding: 2px; text-align: center; font-size: small;">Resolution</div> <div style="text-align: center; margin: 5px 0;">  </div> <div style="background-color: black; color: white; padding: 2px; text-align: center; font-size: small;">12VDC</div> <div style="background-color: black; color: white; padding: 2px; text-align: center; font-size: x-small;">Operating Voltage</div>
Signal System	NTSC/PAL	
Horizontal Resolution (D/N)	550 TVL day / 600 TVL night	
Image Sensor	1/3" CCD	
Picture Elements	NTSC: 768 (H) x 494(V) PAL: 752 (H) x 582 (V)	
Lens	3.7 mm fixed	
FOV Degrees (Horizontal/Vertical)	65.9° (H)/51.8° (V)	
Auto Iris	-- --	
Min. Illumination (day)	Color (day) 0.1 lux f1.2	
Min. Illumination (night)	B/W (night) 0.01 lux f1.2	
IR Beam Distance	-- --	
Infrared	-- --	
Day/Night (Electronic)	Yes	
True Day/Night	-- --	
Scanning System	2:1 interlaced	
Signal-to-Noise Ratio	≥50 dB (AGC off)	
Synchronization	Internal	
Gamma Correction	0.45 approx.	
Back Light Compensation	Yes	
White Balance	Yes	
On-Screen Display	-- --	
Extra Spot Monitor Output	-- --	
PoUTP	-- --	
DNR /Digital Noise	-- --	

Reduction)	
WDR (Wide Dynamic Range)	-- --
IR Cut Filter (Mechanical)	-- --
3 Way Axis Gimbal	-- --
Communication	-- --
ACCESSORIES	
Bracket	-- --
Sun Shield	-- --
Remote Control	-- --
Power Pigtail Lead	-- --
ENVIRONMENTAL	
Operation Temperature	14°F to 122°F (-10°C to 50 °C)
Storage Temperature	-22°F to 140°F (-30°C to 60 °C)
Operating Humidity	Up to 95%
Ingress Protection Rating (IEC 60529)	-- --
Weatherproof	-- --
Vandal Proof	-- --
ELECTRICAL	
Video Out	Composite signal 1.0Vp-p/75ohm
Signal Connector	BNC
Input Voltage	12 VDC
Current Draw	200 mA
Power Consumption	1 Watt
PHYSICAL	
Dimensions (W x H)	10.63" ø x 1.58" (270 x 40 mm)
Weight	1.26 lb (570 g)
Housing Material	Plastic
Housing Color	Black
Camera Mounting	Wall
REGULATORY	
Regulatory Type	CE, FCC, UL

Warranty

5 Years