






## Analog Dome Camera

- 700 TVL color dome camera
- 2.8~11 mm varifocal lens
- Weatherproof (IP66) & Vandal proof
- Wide Dynamic Range
- True day/night & Auto iris
- Dual voltage



Bravo camera series offers superior imaging quality along with a wide selection of superior camera enclosures engineered by Aventura. The Bravo Series cameras have been setting the standards for image perfection. Bravo series cameras excel in challenging low light conditions and are constructed of the finest materials and are ruggedized to withstand the elements. Bravo cameras are available in a variety of lenses and enclosures to meet the requirements of professional CCTV integrators. Most Bravo cameras come with an unprecedented 10-year warranty.

Style	Vandal proof dome	<div style="background-color: orange; color: black; padding: 5px; text-align: center;"><b>700 TVL</b></div> <div style="background-color: black; color: white; padding: 2px; text-align: center; font-size: small;">Resolution</div> <div style="background-color: green; color: black; padding: 5px; text-align: center;">  </div> <div style="background-color: black; color: white; padding: 2px; text-align: center; font-size: small;">Auto Iris</div> <div style="background-color: green; color: black; padding: 5px; text-align: center;">  </div> <div style="background-color: black; color: white; padding: 2px; text-align: center; font-size: small;">Varifocal</div> <div style="background-color: blue; color: white; padding: 5px; text-align: center;">  </div> <div style="background-color: black; color: white; padding: 2px; text-align: center; font-size: small;">Day/Night</div> <div style="background-color: blue; color: white; padding: 5px; text-align: center;">  </div> <div style="background-color: black; color: white; padding: 2px; text-align: center; font-size: small;">TRUE Day/Night</div> <div style="background-color: yellow; color: black; padding: 5px; text-align: center;">  </div> <div style="background-color: black; color: white; padding: 2px; text-align: center; font-size: small;">OSD MENU</div>
Signal System	NTSC/PAL	
Horizontal Resolution (D/N)	700 TVL day / 750 TVL night	
Image Sensor	1/3" Double Scan Super HAD II CCD	
Picture Elements	NTSC:976(H)X494(V) PAL:976(H)X582(V)	
Lens	2.8~12 mm varifocal	
FOV Degrees (Horizontal/Vertical)	81.2°(H)/65.4°(V)~24.6 (H)/18.5°(V)	
Auto Iris	Yes	
Min. Illumination (day)	Color (day) 0.1 lux f1.3	
Min. Illumination (night)	B/W (night) 0.0001 lux f1.3	
IR Beam Distance	-- --	
Infrared	-- --	
Day/Night (Electronic)	Yes	
True Day/Night	Yes	
Scanning System	2:1 interlaced	
Signal-to-Noise Ratio	≥50 dB (AGC off)	
Synchronization	Internal	
Gamma Correction	0.45 approx.	
Back Light	Yes	

Compensation		
White Balance	Yes	Wide Dynamic
On-Screen Display	-- --	
Extra Spot Monitor Output	-- --	3-Way Gimbal
PoUTP	-- --	
DNR (Digital Noise Reduction)	Yes	IP66 Weather-Proof
WDR (Wide Dynamic Range)	Yes	
IR Cut Filter (Mechanical)	Yes	Vandal-Proof
3 Way Axis Gimbal	Yes	
Communication	-- --	12VDC/24VAC Dual Voltage
<b>ACCESSORIES</b>		
Bracket	-- --	
Sun Shield	-- --	
Power Pigtail Lead	Yes	
<b>ENVIRONMENTAL</b>		
Operation Temperature	14°F to 122°F (-10°C to 50 °C)	
Storage Temperature	-22°F to 140°F (-30°C to 60 °C)	
Operating Humidity	Up to 95%	
Ingress Protection Rating (IEC 60529)	IP66	
Weatherproof	Yes	
Vandal Proof	Yes	
<b>ELECTRICAL</b>		
Video Out	Composite signal 1.0Vp-p/75ohm	
Signal Connector	BNC	
Input Voltage	12 VDC/24 VAC	
Current Draw	260 mA	
Power Consumption	3.1 Watts	
<b>PHYSICAL</b>		
Dimensions (W x H)	5.6" ø x 5" (143 x 128.5 mm)	
Weight	2.42 lb (1.1 kg)	
Housing Material	Zinc	
Housing Color	White	
Camera Mounting	Wall/ceiling	
<b>REGULATORY</b>		
Regulatory Type	CE, FCC, UL	

## Warranty

10 Years